

TESON MASTIC - PROFESSIONAL READY TO USE TILE ADHESIVE (TM-321)

Description: Teson Mastic is a professional grade proprietary water-based adhesive for setting glazed and unglazed ceramic and porcelain tiles on walls, floors and countertop. This adhesive is used for interior application only.

Application:

- Walls and floors
- Porcelain mosaics
- Gypsum wallboard
- Wall, dry backsplash
- Glazed and unglazed tile
- Fully cured concrete substrate
- Kitchen and bathroom wall (Not adjoining a shower and tub)

Advantages:

- Low in odor
- Extended open time
- Meet D1TE standard
- Smooth and easy to spread
- Excellent grab up to 30 x 30 cm tile
- Ready to use, no mixing is required



Application Reference:



Apply Teson Mastic



Mosaic Installation



Counter Top Installation

Product Range:

PRODUCT CODE	PACKING SIZE	PACKING FORM	COLOUR
TM-321/LG/20K	20KG	Pail	Light Grey
TM-321/LG/5K	5KG	Pail	Light Grey
TM-321/LG/1K	1KG	Can	Light Grey



TESON MASTIC - PROFESSIONAL READY TO USE TILE ADHESIVE (TM-321)

on Mastic is a professional grade proprietary water-based adhesive fo<mark>r setting</mark> glazed and unglazed ceramic and porcelain tiles on Ils, floors and countertop. This adhesive is used for interior application only.

PLICATION:

/alls and floors
orcelain mosaics
ypsum wallboard
/all, dry backsplash
lazed and unglazed tile
ully cured concrete substrate
itchen and bathroom wall
Not adjoining a shower and tub)

VANTAGES:

ow in odor xtended open time Aeet D1TE standard mooth and easy to spread xcellent grab up to 30 x 30 cm tile leady to use, no mixing is required

PRODUCT APPLICATION:

- Use a typical notched trowel with sufficient depth to ensure proper transfer, expering at least 85% of the tile back.
- Using the trowel's flat edge to spread the adhesive onto the substrate.
- Apply additional material and comb the adhesive in one direction using the trowel's notched side to achieve an even-setting bed.
- Do not spread more adhesive than can be covered with tiles within 30 to 45 minutes.
- If skinning occurs, scrape off skin and replace with fresh adhesive.
- ace tiles firmly in position on the fresh adhesive. Push the tile back and forth a direction perpendicular to trowel ridges, in order to collapses the dhesive ridges and achieve maximum coverage.
- ensure proper contact between the fresh adhesive, tile and substrate by periodically lifting a few tile to check for acceptable coverage.
- Wake all alignment and adjustment immediately (Don't exceed 45 minutes). Promptly use water to clear smudges from the face of the tiles while alhesive still fresh. Once adhesive has dried, clean with white spirits.

APPROXIMATE COVERAGE:

- 3 x 3 x 3mm typical trowel for mosaic will achieve 1.3 to 1.5 sq-m coverage.
- 6 x 6 x 6mm typical trowel for tile between 10 x 10cm and 30 x 30cm will achieve 0.5 to 0.8 sq-m coverage.

COLOUR:

· Light grey.

SHELF LIFE / STORAGE:

- 12 Months.
- · Do not store directly under sunlight and when it's likely to freeze.

LIMITATIONS:

- Do not use for exterior and area subjects to water immersion.
- Use at temperature between 5°C and 35°C.
- Do not use to set natural stone.

PRODUCT RANGE:

	PRODUCT CODE	PACKING SIZE	PACKING FORM	COLOUR
	TM-321/LG/20K	20KG	Pail	Light Grey
۱	TM-321/LG/5K	5KG	Pail	Light Grey
	TM-321/LG/1K	1KG	Can	Light Grey

APPLICATION REFERENCE:



Apply Teson Mastic



Mosaic Installation



Counter Top Installation

NITED WARRANTY:

er and manufacturers only obligation shall be replacement of such quantity of product proved to be defective. All advice given herewith is to be the best of wledge, true and accurate. All recommendations or suggestions are made without guarantee. Since the condition of use are beyond our control, the seller or nufacturer shall not be liable for any injuries, loss or damage, direct or consequential arising from the use of or the failure of the product. Before using, user shall ermine the suitability of the product for his intended use and user assumes all risk and liability.