

	EXCEL INGENIOUS SDN. BHD.	Issue Date: 16.06.2026
	Technical Data Sheet	Revision Date: - Revision No: 0



TM-402 TESON WHITE CREAMY TILE GROUT



PRODUCT DESCRIPTION

TESON White Creamy Tile Grout is a ready-to-use acrylic-based tile grout specially formulated for filling tile joints in interior and exterior applications. The product provides a smooth creamy white finish with excellent anti-sag properties and good workability for vertical and horizontal joints.

FEATURES

- Ready-to-use
- Creamy white appearance
- Excellent workability
- Non-sag formulation
- No streak formation after curing
- Smooth finishing
- Good filling capability
- Easy application and clean-up

APPLICATIONS

- Ceramic tile joints
- Porcelain tile joints
- Mosaic tile joints
- Interior wall and floor applications
- Exterior wall applications
- Bathroom and kitchen tiling works

TECHNICAL DATA

Properties	Specifications	Method
Appearance	White Creamy Paste	Visual
Specific Gravity	1.40 – 1.50	ASTM D1475-13
Solid Content, %	≥ 80	In-House Test
Viscosity, cps @ 10rpm, Spindle 6, 25°C	460,000 ± 50,000	ASTM D2983-22
Shore A Hardness	≥ 70	ASTM D2240
Sag Resistance	No Sag	In-House Test
Streak Formation	None Observed	In-House Test

These figures are only intended as a guide and should not be used in preparing specifications.

DIRECTION OF USE

Surface Preparation

- Ensure tile joints are clean, dry and free from dust, grease, oil and loose materials.
- Remove any excess adhesive from the joints before grouting.

Application

1. Stir the grout thoroughly before use.
2. Apply using a rubber grout float or putty knife.
3. Force grout into tile joints completely.
4. Remove excess material from tile surfaces.
5. Clean tile surface with a damp sponge before the grout fully dries.
6. Allow sufficient drying and curing time before exposing to water.

	EXCEL INGENIOUS SDN. BHD.	Issue Date: 16.06.2026
	Technical Data Sheet	Revision Date: -
		Revision No: 0

Coverage

Coverage varies depending on:

- Tile size
- Tile thickness
- Joint width
- Joint depth

A site trial is recommended to determine actual consumption.

For technical, quality, or product safety questions, please contact:

EXCEL INGENIOUS SDN. BHD.

No. 2, Jalan IM 3/6, Kawasan Perindustrian IM 3, Bandar Indera Mahkota, 25200 Kuantan, Pahang, Malaysia.

sales@teson.co

<https://teson.co>

Drying & Curing

Condition	Typical Time
Surface Dry	1 – 2 Hours
Light Traffic	24 Hours
Full Cure	7 Days

(At 25°C and 60% RH)

PACKAGING

Packaging Type	Weight	Per Carton
Round Pail	1.3 KG	12 pcs

STORAGE & SHELF LIFE

Store in a dry and cool place at temperatures between 5°C to 30°C in unopened-original package for a shelf life of 12 months. Protect against moisture and direct sunlight.

SAFETY NOTES

Read and understand Safety Data Sheet of this product before handling or using.

Keep out of reach of children.

The information and data contained herein is believed to be accurate and reliable: however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses or the conditions of use to which this product may be put, no warranties concerning fitness or suitability for a particular use or purpose are made. The supplier warrants only that its products will meet its specifications. There is not a warranty of merchantability or fitness for use, nor any other express or implied warranty. The user's exclusive remedy and supplier's sole liability is replacement of any product shown to be otherwise than as warranted.