



REVISION ON :

## CSM FIBER (TWT-011/CSM/50M)

### Product description:

Chopped strand mat (CSM) 100g/m<sup>2</sup> is a mat mix with resin. It is lightweight, extremely strong.

### Product Use :

CSM FIBER is an inorganic non-metal material and is used as reinforcement for thermoplastic and thermosetting resins.

### Uses :

Roof coating waterproofing, boats, automobiles, bath tubs, water tanks, pipes, cladding.

### Features :

- Very high smoothness of the laminate surface.
- Good compatibility with vinyl ester and resins.
- High suitable for layer with coating.

**Roll weight :** 5kg

**Size :** 50m per roll - 4 rolls per box with 12 boxes or 48 rolls per pallet

### PHYSICAL PROPERTY :-

Product Appearance And Properties	White or off-white solid, No odor.
pH Value	No applicable
Melting Point	>800°C
Boiling Point	Not applicable
Relative Density	2.6 Times that of water
Relative Vapor Density	Not applicable
Flash Point	Not applicable
Ignition Temperature	Not applicable
Explosion Upper Limit	Not applicable
Explosion Lower Limit	Not applicable
Solubility (In Water)	Insoluble
Stability	Stable material
Material To Avoid	None
Conditions To Avoid	None
Hazardous Polymerization	Will not occur

**EXCEL INGENIOUS SDN. BHD. (1045163-X)**

NO.2A, JALAN IM 3/6, KAWASAN PERINDUSTRIAN MAHKOTA, 25200 KUANTAN, PAHANG DARUL MAKMUR,  
MALAYSIA. TEL : 09-572 1063/64/65 FAX : 09-572 1066.